

**Product Specification**

Customer		Outline	
Product Name	Part No.	Customer Code	Picture No.
IP - PDU	CR021H4226		
Main Function	Parameter		Remark
Monitor	Total load current		
	Input Voltage		
	Total energy consumption (kWh)		
	Power Factor		
	Total power(kW)		
	Temperature and Humidity state (1pcs T/H sensors on standard version)		
Configure	Set the email alarm address		
	Set the threshold of total load current		
	Set the threshold of temperature and humidity		
	Set SNMP V,HTTP		
	Set network parameters (IP, gateway, subnet mask, DSN)		
Alarm	System alarm	Overload happens	
	User -defined alarm	Threshold of total load current is exceeded	
		Threshold of temperature and humidity is exceeded	
	Alarm method	Buzzer beeping	
		Send email to administrator automatically	
		SNMP send Trap alarm information	
Central management		Support central management of N units via Clever Manager software	
Access method		Web based, access via IE	
		Serial port	
		Daisy-china port	
		SNMP V1 support	
User management		User name and password configurable	
Software system		Support web browsers like IE, Fire fox, Google, support software update	
Input/output			
Input	Rated input	230V~50/60 Hz	
	Input terminal type	IEC60309 plug (32A 2P+E)	

	Cable specification	3×6.0mm ² ;				
	Cable length	3 M				
	The max input	32A				
Output	Outlet standard	IEC320 C13 socket	Rated current	10A	Outlet quantity	36way
	Outlet standard	IEC320 C19 socket	Rated current	16A	Outlet quantity	6 way
	Rated output	230VAC				
Dimension	Product size	L×W×H = 1785 x 68 x 44.4 mm				
  <p>IEC60309 plug (32A 2P+E)</p>						
Design:	Customer confirm:	Check:	Authorized:			