



**RA018H2426 Specification**

Customer		Outline	
Product Name		Factory Part No.	Customer Part No.
RPDU		RA018H2426	
Main Functions		Details	
Monitor		Total load current	
		Input Voltage	
		Total energy consumption (kWh)	
		Power Factor	
		Total power(kW)	
		Temperature and Humidity state (Max. 2 T/H sensors on standard version)	
Control and configure		Set the threshold of total load current	
		Clear the total energy consumption(kWh)	
		Set the threshold of temperature and humidity	
		Set the work mode (master or slave)	
		Support external WIFI,HTTP,HTTPS ,SYSLOGS,NTP,FTP,SMTP,IPV4	
Alarm	User defined alarm	Set the threshold of total load current	
		Set the threshold of temperature and humidity	
	System default alarm	When overload occurs	
	Alarm method	LCD displays the alarm and buzzer sounds	
		Web interface show the value exceeded in red	
		Send E-mail to administrator automatically	
		SNMP sends trap alarm information	
		SYSLOGS	
Log record		Record and save the operating and alert information, graphic record of electric parameters and environment which can be exported.	
Daisy chain		Support Daisy-chain	
Central management		Support central management of N units via CLEVER Manager software	
User management		Different user permission configuration	
		Outlet Alarm permission configuration	

	Set the permission to clear the energy consumption(kWh)					
Additional function	Support software update through USB port & FTP method					
	LCD display on/off switch					
	LCD display rotary switch					
	Stop buzzer alarm					
	Support Multi-language display					
Accessing method	Web based, support multiple browsers like IE, Google, Firefox etc.					
	SNMP (V1/V2C/V3)					
	Telnet, SSH					
	Serial Access, Modbus					
	RADIUS,					
Input/output						
Input	Rated input voltage	230V~ 50/60 Hz				
	Input terminal type	IEC60309 2P+E 32A plug				
	Cable specification	3×6.0mm ² ;				
	Cable length	3M				
	The max input current	32A				
Output	Socket	IEC320 C13	Rated current	10A	Outlet	18
	Socket	IEC320 C19	Rated current	16A	Outlet	6
	Rated output voltage	230VAC				
Dimension	Product size	L×W×H = 1850×56×52mm				
Optional fittings						
Temperature/humidity sensor		Door sensor	Smoke sensor		Water sensor	
		Customized solution, must ask before production.				
PDU drawing on next page						



PDU overview



IEC60309 2P+E 32A plug

Design:	Customer confirm:	Check:	Authorized:
---------	-------------------	--------	-------------